



Standard configuration:

- Tractor 3-pt. linkage cat. I + II
- PTO speed 540 rpm
- Walterscheid PTO shaft
- Low, streamlined profile and round sides
- 1 or 2 front support wheels and 1 (Model T-155) or 2 rear rollers with conical ends and special covers over the bearings
- Indirect and flexible V-belt drive (most belts with automatic spring loaded tensioner)
- Generously overlapping, replaceable and reversible swing-away blades

Perfect 'T' model mower

The Perfect 'T' series mower has been specifically designed for a neat upkeep of grass in modern orchards and vineyards.

In order to prevent damage to low hanging branches and fruit, it has an extra low and streamlined construction, along with smooth rounded sides.

The mower works closely behind the tractor, making handling easy even if room is limited.

Either one or two front support wheels and rear rollers give the necessary stability and excellent terrain adjustment.

All generously overlapping cutting blades are driven indirectly by 'V' belts, mostly with automatic spring-loaded belt tensioners.

This flexible drive system protects the gearbox from shock loads.

Optional:

- Mow-spray-combination feature: with standard gearbox or with disconnectable gearbox
- Front mounted models
- Front and rear mounted models
- 2 Front swivel wheels instead of 1 fixed wheel (Standard on T-225, T-250, T-290)

Specifications	T-155	T-180	T-200	T-225	T-250	T-290
Cutting width cm/inch	155/5'1"	180/5'11"	200/6'7"	225/7'5"	250/8'2"	290/9'6"
Minimum power required at 540 rpm of PTO kW/HP	16/22	18/25	22/30	26/35	29/40	33/45
Number of blades	3	3	3	3	3	3
Total width cm/inch	160/5'3"	185/6'1"	205/6'9"	230/7'7"	255/8'4"	295/9'8"
Cutting height cm/inch	4-10/1½-4	4-10/1½-4	4-10/1½-4	4-10/1½-4	4-10/1½-4	4-10/1½-4
Length of rear roller(s) cm/inch	(1) 102/40"	(2) 38/15"	(2) 48/19"	(2) 53/21"	(2) 53/21"	(2) 53/21"
Weight kg/lbs	280/615	305/670	330/725	370/815	380/840	450/990

E&OE

NP Seymour Ltd, Avon Works, Cranbrook, Kent, TN17 2PT.

Tel: 01580 712200

E-mail: sales@npseymour.co.uk Web: www.npseymour.co.uk