



Perfect mowers, pulverisers and brush sweeps are renowned for their build quality, durability and long life. Van Wamel in Holland have been designing and manufacturing machines since 1960's so have learnt a lot about what farmers require.

## Perfect heavy duty topper model KT

Heavy-duty model with more internal clearance for greater capacity and heavier body to deal with longer and/or denser vegetation in fallow land or cornstalks etc.

Ideal for farmers who need a professional, versatile and reliable machine giving them excellent performance at a low maintenance cost.

Easily adjustable rear hood is fitted as standard. It can be used closed for maximum mulching of material. When open the material will be less mulched, but faster working speed can be maintained.



Technical specifications		KT-245	KT-270	KT-300	KT2-320
Cutting width	cm/ft	245 / 8'1"	270 / 8'10"	300 / 9'10"	320 / 10'6"
PTO speed	cm/ft	1000	1000	1000	1000
Flail rotor speed	rpm	2100	2100	2100	1750
*Power requirements, minimal	kW/HP	40 / 55	48 / 65	55 / 75	62 / 85
Flails - standard 0,8 kg = 1¾ lb each - option 2,2 kg = 5 lb each		24	28	32	32
		16	16	18	20
Overall width	cm/ft	274 / 8'12"	299 / 9'10"	329 / 10'10"	349 / 11'6"
Tractor 3 pt. linkage: std.	cat.	II	II	II	II
Weight	kg/lbs	900 / 1980	970 / 2135	1030 / 2265	1095 / 2415
Offset from tractor centreline:					
Fixed linkage (standard)	cm/ft	143 / 4'8"	168 / 5'6"	150 / 4'11"	160 / 5'3"
Manual or Hydr. Side-Shift (optional):					
- minimum	cm/ft	115 / 3'9"	140 / 4'7"	122 / 4'0"	132 / 4'4"
- maximum	cm/ft	172 / 5'8"	197 / 6'6"	180 / 5'11"	190 / 6'3"

\*Power requirements depend entirely on the type of work. The cutting height is adjustable from 4 to 10 cm (1½" to 4")  
A PTO shaft with overload protection must be used in case of oversized tractors

### Optional:

- 540rpm PTO
- Front mounting
- Hydraulic or manual offset
- 2 pneumatic rear wheels
- Heavy duty flails